

Product Description

Carpet Description:	Nylon Carpet Tile
Construction:	Tufted Textured Loop
Face Fiber:	100% Nylon BCF Solution-dyed
Pile Height / Carpet Thickness:	4.0mm (+/-0.3mm)
Total Height:	6.5mm (+/-0.3mm)
Pile Weight:	460g/sq.m (+/-5%)
Gauge:	1/12"
Primary Backing:	Non-woven Polyester Spunbonded
Secondary Backing:	PVC with Glass Fiber
Width:	50 x 50cm Tile

Testing

CRI Green Label Plus:	GLP1879	
Colorfastness to Light:	AATCC 16-03	Rating 5.0
Colorfastness to Water:	AATCC 107-02	Rating 5.0
Colorfastness to Cleaning:	AATCC 138-00	Rating 5.0
Colorfastness to Crocking:	AATCC 165-99	Rating 5.0
Stain Resistance:	AATCC 175-03	Rating 10
Compression force deflection:	ASTM D 3574	80.7 Lbs/inch ²
Smoke density (flaming):	ASTM E 662	102
Smoke density (non-flaming):	ASTM E 662	424
Loose laid:	BS 4790-1987	Low Radius
Edge Ravel:	ASTM D 7267	0.5 Lbs
Surface Flammability:	ASTM D 2859	DOC FF 1-70
Radiant Flux:	ASTM E 648	Class I
Tuft bind:	ASTM D 1335	10.6Lbs
AACHEN dimensional stability:	ASTM D 7570	MT4: 0.091% CT4:0.008%
Electrostatic propensity:	AATCC 134	0.5kv
Accelerated soiling:	Accelerated soiling	Rating 5.0
Wear warranty:	10 Years	



Durable



Anti-static



Quality



Heavy Traffic



Fade Resistant



Stair Friendly

